



Next Generation Automotive Mobility Technology

Innovative n-Wheel Technology Based on an Architectured Cellular Metamaterial

N-Wheel Technologies, Inc.

Ann Arbor, Michigan www.n-wheel.com

- Novel
- Non-Pneumatic
- Negative Poisson's Ratio Meta-Material



PART-I

Background

History of Pneumatic Tires



1844 – Vulcanized rubber (Charles Goodyear)

1888 – Pneumatic tires for bicycles (John Dunlop)

1890 – Wheel rim (CK Welsh)

1908 – Grooved tires (Frank Seiberling)

1954 – Tubeless tire (Packard)



John Dunlop







Charles Goodyear





Frank Seiberling

- The current rubber tire technology has been in use for over 70 years
- Pneumatic tires widely regarded as the standard for automotive vehicles.



1954 Packard Clipper

Global Tire Market Forecast



- ➤ The global tire market is expected to grow significantly, reaching approximately \$280 billion by 2024, up from \$239 billion in 2019. By 2028, the market is projected to hit \$374.51 billion, with a compound annual growth rate (CAGR) of 7.42% (2023–2028).
- Key drivers include:
 - Increased vehicle production, especially in developing regions.
 - Growth in electric and autonomous vehicles.
 - Advancements in tire technology and materials.
- ➤ When combined with the wheel rim market, the total tire-wheel market is even larger, with the wheel rim market alone projected to reach \$78 billion by 2028. This estimate excludes related sectors such as tire and rim manufacturing equipment and new assembly lines.

Disadvantages of Pneumatic Tires



- Susceptibility to Punctures: Easily punctured by sharp objects, leading to flats and necessary repairs.
- Vulnerability to Damage: Prone to damage from impacts like potholes or curbs, causing sidewall issues or blowouts.
- Maintenance Requirements: Requires regular air pressure checks and maintenance to prevent poor performance and wear.
- Temperature Sensitivity: Air pressure fluctuates with temperature, needing frequent adjustments.
- Durability: Shorter lifespan than solid tires due to wear, requiring consistent upkeep.
- Weight: Difficult to reduce, affecting fuel efficiency and performance.
- Cost: Higher long-term costs due to repairs, replacements, and maintenance.

Non-Pneumatic Tire Technologies









Michelin Tweel (2005)

Bridgestone Airless Tires (2011) Resilient Technologies (2008)

- Non-pneumatic tires have existed since 2005.
- Leading tire companies are actively developing them.
- Michelin's Tweel is already in mass production.
- GM and Michelin announced plans to equip passenger cars with Uptis in 2024.
- Michelin proclaims the "Second Wheel Revolution" is coming!



Hantai Flexairless Tire (2013)

Advantages of Non-Pneumatic Tires



- Puncture-Proof: Non-pneumatic tires resist punctures and flats since they contain no air, making them ideal for rough terrain.
- Low Maintenance: No need for air pressure checks or adjustments, reducing upkeep.
- Durability: Made from solid materials or advanced composites, they last longer and resist wear.
- **Stability:** Consistent performance unaffected by air pressure, ensuring reliability under varying loads and temperatures.
- Cost-Effective: Lower long-term costs due to durability and minimal maintenance.
- Eco-Friendly: Often made from recyclable materials, reducing environmental impact.
- Extreme Performance: Reliable in harsh conditions where pneumatic tires may fail.
- Enhanced Safety: Eliminates blowout risks, improving safety for vehicles and equipment.


- Limited Speed and Load Capacities: Non-pneumatic tires typically have lower speed and load ratings, making them unsuitable for high-speed or heavy-load applications.
- Reduced Ride Comfort: The absence of air cushioning leads to less effective shock absorption, resulting in a rougher ride and increased vibrations.
- Inferior Traction and Handling: Non-pneumatic tires may underperform in traction and handling compared to pneumatic counterparts.
- Design and Aesthetic Challenges: Limited flexibility in design and less appealing aesthetics may influence consumer preferences.
- Limited Availability and Compatibility: Non-pneumatic tires are not as widely available and may lack compatibility with many vehicle types, limiting their adoption.
- Increased Weight: Heavier construction can negatively impact fuel efficiency and overall vehicle performance.
- Higher Costs: Advanced materials and manufacturing processes may result in higher initial costs, which can deter potential buyers.



Developing new and advanced materials is the key to the successful innovation of airless tires!

Lightweight and High-Performance Materials






N. A. Fleck, V. S. Deshpande, M. F. Ashby

Tendency of New Material Development






Millimeter


Architectured Cellular Metamaterials (ACM)

Larger-scale


Lattice materials

Cellular materials





Micro-Nano-truss Metallic foam Honeycomb Sandwich




Graphene

Nanotube

Micro-Architectured Cellular Materials


Nano-


Nanotube Graphene Fiber-reinforced composites



Materials to be Architectured in Larger Scale








Example ACM Materials



Architectured Cellular Metamaterials (ACM)



3D Printed ACM Materials



Architectured Cellular Metamaterials (ACM)





Features of ACM Materials



- Efficient Usage:

 Eliminates wasteful
 material.
- Porous-Solid Mix:
 Balances structure and performance.
- Multi-Material: Combines diverse parent materials.
- Architectural Design:
 Optimized for functionality.
- Lightweight Performance:
 High strength, low weight.





Three ACM Materials We Developed



Negative Poisson's Ratio Masteries


NPR

Biomimetic Tendon-Reinforced Materials

BTR

Advanced Composite
Armors

ACA



High-performance & lightweight components

New body structure

Blast & ballistic protection

3D NPR-ACM Material


NPR (Negative Poisson's Ratio) Material

U.S. Patent


- **Patent Number:** US 7,910,193 B2
- Effective Date: March 22, 2011
- Other Related Patents

Key Features:

- Shrinks under pressure, expands under tension
- Strengthens with increased pressure
- Exceptional energy absorption
- Customizable functional design
- Unique, irreplaceable advantages
- Wide application potential




Compressive shrinkage phenomenon





Sample of engineering NPR material

Metallic ACM Developed at MKP Inc.











Three-Dimensional NPR Material






Variability in the Properties of NPR Materials V





a)
$$\theta_1 = 60^{\circ}$$
, $\theta_2 = 120^{\circ}$

Negative Poisson's Ratio = -0.96 Young's Modulus = 1.4e3 Material Density = 36.7%




b)
$$\theta_1 = 30^{\circ}$$
, $\theta_2 = 60^{\circ}$

Negative Poisson's Ratio = -7.4 Young's Modulus = 2.7e3 Material Density = 36.5%


Broad Material Property Coverage





Functionally-Graded Material Design







The integrated structure's properties are E = 2.8GPa, v = -0.24

Animation of Deformed Shape Under a Blast Force









Special Properties of the NPR Material






1) Adaptive stiffening under load



Made of steel 8 10 12 14 16 18 20

Long arm thickness (mm)

2) Broad material property coverage



4) Impact energy absorption

Potential Applications of the NPR Material



Lightweight anti-collision energy absorption components





- NPR non-pneumatic tires
- Anti-explosion energy absorption materials
- Deployable structures
- NPR stents
- ...






















PART-II

Technology Developed (n-Wheel)


Our New Technology: metaTire™ & n-Wheel™

- In 2010, we developed metaTire™, a revolutionary non-pneumatic tire based on our patented NPR (Negative Poisson's Ratio) metamaterial. It offers multiple advantages over traditional materials, including adaptive stiffening under load, superior impact energy absorption, broad material property coverage, and enhanced design flexibility for diverse applications.
- When integrated with a wheel rim system, it becomes n-Wheel™, which has been road-tested in various vehicles, including an ATV, TUV, 3.5-ton forklift, and SUV.
 More details will be provided in later slides.
- The metaTire™/n-Wheel™ concept significantly expands the design and application possibilities for non-pneumatic tires, surpassing existing solutions.
- The goal of n-Wheel™ is to deliver lighter weight, extended tire lifespan, and superior performance in drivability, durability, NVH (Noise, Vibration, and Harshness), load capacity, fuel efficiency, and design flexibility, compared to both pneumatic and non-pneumatic tires.

Application to the metaTire[™] & n-Wheel[™]




US patent: 7,910,193





Example RUV Application

US patent: 7,910,193





Physical Prototype

Awarded Patents



(10) Patent No.: US 8,544,515 B2

*Oct. 1, 2013

| Ma et al. | | | | |
|-----------|--|------|--|--|
| | | | | |

(12) United States Patent

(54) ULTRALIGHTWEIGHT RUNFLAT TIRES BASED UPON NEGATIVE POISSON RATIO (NPR) AUXETIC STRUCTURES

(75) Inventors: Zheng-Dong Ma, Ann Arbor, MI (US); Yuanyuan Liu, Ann Arbor, MI (US); Xiaoming Liu, Ann Arbor, MI (US); Ce Sun, Ann Arbor, MI (US); Yushun Cui, Ann Arbor, MI (US)

(73) Assignce: MKP Structural Design Associates,

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 304 days.

This patent is subject to a terminal dis

Prior Publication Data

US 2011/0168313 A1 Jul. 14, 2011

Related U.S. Application Data

Continuation-in-part of application No. 12/267,867, filed on Nov. 10, 2008, now Pat. No. 7,910,193.

(52) U.S. CL

. 152/450; 152/151; 152/152; 152/516

(45) Date of Patent:


U.S. PATENT DOCUMENTS 0.5. PALENT IDA-UMINI S 4,668,557 A \$11957 Lakes \$3855,597 A \$11959 Jayazaman 6,097,944 B2 22006 Harrison et al. 7,160,621 B2 12/007 Chaudhari et al. 7,160,621 B2 12/007 Chaudhari et al. 7,160,621 B3 12/007 Vou 2007/0213838 A1* 9,2007 Hengelmolen 2010/01979 A1* \$2000 Ms 2011/0240190 A1* 10/2011 Summers et al.

* cited by examiner

Primary Examiner - Justin Fischer

ABSTRACT

Negative Poisson's ratio (NPR) or aux lightweight wheels and runflat tires. T tailored and functionally-designed to op flat requirements for both military and NPR-runflat tires may be fabricated usi and simple manufacturing processes, and high-volume production. In prefer and nign-volume production. In preser-runflat tire designs are fully compatib Inflation Systems (CTIS), while prov-equivalent to current military vehicle so weight. An auxetic wheel according to prises a line defining an axis of rotatic entric rings of unit cells surroundi cell being constructed of a plurality of Negative Poisson's Ratio (NPR) struc ring of unit cells is arranged to facilitat tact, such that the stiffness of the struc region of loading due to terrain contact rotates. A layer of material may be d concentric rings of unit cells which in pr comprise a plurality of nested-V shar provided over the outermost ring of un which may, or may not, be inflated.



(10) Patent No.: US 10,315,459 B2

(12) United States Patent

(54) ULTRALIGHTWEIGHT AIRLESS ATV WHEELS BASED UPON NEGATIVE POISSON RATIO (NPR) AUXETIC STRUCTURES

(72) Inventor: Zheng-Dong Ma, Ann Arbor, MI (US) Subject to any disclaimer, the term of thi patent is extended or adjusted under 35 U.S.C. 154(b) by 39 days.

US 2017/0015134 A1 Jan. 19, 2017

Related U.S. Application Data

visional application No. 62/191,736, filed on Jul.

Prior Publication Data

(51) Int. CL B60B 1/00 B60B 9/26 B60B 5/02 B60C 7/10 B60C 7/16 (2006.01)

(52) U.S. CL CL. B60B 1/006 (2013.01); B60B 5/02 (2013.01); B60B 9/02 (2013.01); B60F 7/02 (2013.01); B60F 7/02 (2013.01); B60F 7/02 (2013.01); B60F 7/02 (2013.01); B60B 7/00.01 (2013.01); B60B 7/00.01 (2013.01); B60B 7/00.01 (2013.01); B60B 7/00.01 (2013.01); D72T 1/086 (2013.01)

(45) Date of Patent:

References Cited


U.S. PATENT DOCUM

2/2009 Ma 7/2009 Ma 4/2010 Ma 3/2011 Ma 10/2013 Ma et al. 6/2016 Ma 8/2016 Ma 10/2011 Dutton ...

Primary Examiner — S. Joseph Morat Assistant Examiner — Jean W Charles (74) Attorney, Agent, or Firm — John

ABSTRACT

(57) MSTRACT improvements are disclosed regarding which wheels are designed and assent methods wheels are designed and assent of the control 10 Claims, 17 Drawing





(54) AIRLESS AND RUNFLAT TIRE STRUCTURES, COMPONENTS AND ASSEMBLY TECHNIQUES

(71) Applicant: MKP Structural Design Associates,

(72) Inventor: Zheng-Dong Ma, Ann Arbor, MI (US)

Subject to any disclaimer, the term of this U.S.C. 154(b) by 136 days.

(21) Appl. No.: 14/642,846

Prior Publication Data

US 2015/0251493 A1 Sep. 10, 2015

Related U.S. Application Data (60) Provisional application No. 61/950,417, filed on Mar 10, 2014.

(51) Int. Cl. B60C 7/14 B60C 7/08 B60B 9/04 (2006.01) (2006.01)

...... B60C 7/14 (2013.01); B60B 9/04 (2013.01); B60C 7/08 (2013.01); B60C 2007/146 (2013.01)

See application file for complete search history.

(45) Date of Patent:

References Cited

U.S. PATENT DOCUMENTS 1.086,333 A * 2/1914 Russell

4.668,557 A 51987 Lakes 5.855,597 A 11999 Jayazaman 6.997,944 B2 22006 Harrison et al. 7.160,621 B2 12007 Chausthari et al. 7.910,193 B2 32011 Ma 8.544,515 B2 102031 Ma et al. 2006,0265052 A1 112006 Vou 2070/213838 A1 92007 Hengelmolen 2010/0119792 A1 62031 Tercha

2011/0168313 A1* 7/2011 Ma ...


2011/0240190 A1 10/2011 Summers et al. Primary Examiner — S. Joseph Morano Assistant Examiner — Jean Charleston


(74) Attorney, Agent, or Firm - John G. Posa; Belzer PC

ABSTRACT

An auxetic wheel according to the invention comprises a line defining an axis of rotation; and a plurality of concentric rings of unit cells surrounding the axis, each unit cell being constructed of a plurality of members defining a Negative Poisson's Ratio (NPPS) structure. The outermost ring of unit cells is arranged to facilitate rolling terrain contact, such that the stiffness of the structure in the localized region of the stiffness of the structure in the localized region of looding due to terrain contact increases as the wheel rotates. A layer of material may be disposed between the concentri-rings of unit cells which in preferred embodiments comprise a plurality of nested-4 shapes. A cover may be provided over the outermost ring of unit cells forming a tire which may, or may not, be inflatted.

13 Claims, 23 Drawing Sheets









Three Major metaTire Concepts






a) Quasi-3D



b) 3D



c) Super-3D

Patented by N-Wheel Technologies, Inc.

Design Variations of the N-Wheel





a) Two-layer structure

b) Three-layer structure

metaTire Technology to Replace Pneumatic Tites



N-Wheel

Stuffer: High strength, lightweight, fatigue-resistant, low vibration, and low noise material

Tendon: High elasticity, high strength, large deformation, high damping material



metaTire: Non-Pneumatic Tire

- Non-pneumatic, impact-resistant, puncture-free, bulletproof
- Can be manufactured using various methods including Modularized manufacturing
- High speed and high load bearing capacity
- High lateral stiffness

Stuffer: Made of lightweight, high-strength, compressive material: Capable of load-bearing, fatigue resistance, high speed impact, low vibration, low noise, and function-oriented design

Tendon: Made of high elasticity, high damping, tensile material: Impact-resistant, vibration reduction, energy absorption, flexibility, durability, function-oriented design

Tread: Made of high-elasticity with good high-speed and off-road performance, low rolling resistance, function-oriented design material


The Necessity of the n-Wheel Technology




- Can overcome the bottlenecks of traditional pneumatic tires/wheels
- Can completely replace pneumatic tires/wheels
 - Enhanced negative Poisson's ratio characteristics for superior load-bearing and impact resistance
 - Function-oriented design for ride comfort, smoothness, and reduced NVH (Noise, Vibration, and Harshness)
 - Superior lateral stiffness for better handling and stability
 - Greatly expanded design space for diversified innovative products
- Can further revolutionize vehicle structure
- Can be easily designed integrated with hub motors
- Can integrate various sensors to become smart
- Easily achieves active and semi-active control
- Can be used for intelligent transportation systems!



Advantage of NPR Structure Over Beam-like Structure



(a) Beam-like structure buckles under excess load





(b) NPR structure is stiffening under the load


NPR Compares to Honeycomb




NPR













Honeycomb

















Maximal bearing force



















(c) Honeycomb structure is softening under the load

Application Example 1: n-Wheel on RUV





(14 Inch)



(UTV)

Application Example 2: n-Wheel on Fork







(3.5-ton Forklift)

Application Example 3: n-Wheel on BJ-40





Prototypes Developed for the n-Wheel






















Advantages and Potential of the n-Wheel



Unlocking New Horizons in Mobility and Technology

- Load-stiffening NPR characteristics: Offers tailored performance under varying loading conditions.
- Adjustable vertical stiffness: Adapts to load, enhancing ride quality.
- Functional design flexibility: Accommodates a wide range of applications.
- Large design space: Supports diverse applications and innovations.
- Superior lateral stiffness: Improves drivability and vehicle stability.
- Enhanced braking and ride comfort and improves NVH (Noise, Vibration, and Harshness) performance.
- Lightweight and cost-effective: Reduces vehicle weight and manufacturing costs.
- Sensor integration-ready: Supports in-wheel intelligent components like sensors and controls.



PART-III

Supporting Technologies Developed

Core Technologies for the Digital n-Wheel



1. Multi-Scale Analysis (MSA)

Core
Technologies
for the Digital
Twin of nWheel

2. Advanced Isogeometric Analysis (AIGA)

3. CAD/CAE/CAM/PLM (C3P) Integration

4. Size, Shape and Topology Optimization (SSTO)

5. Image Processing for Tread NURBS Generation

Multi-Level Reduced-Order Modeling (M-ROM)

7. 3D-Printing Pass Optimization and Slicing Process

8. Parameterized, Modularized, User-Friendly Graphic User Interface (PMF-GUI)

Isogeometric Analysis (IGA)



- NURBS-Based Accuracy: IGA utilizes NURBS functions to define CAD models as shape functions, ensuring precise geometric representation and eliminating errors, even with minimal parameters.
- Seamless CAE-CAD Integration: IGA bridges the gap between Computer-Aided Engineering (CAE) and Computer-Aided Design (CAD), enabling a unified workflow.
- Manufacturing-Ready Outputs: Optimization results from IGA are CAD models that are directly ready for manufacturing without additional conversion or adjustments.





Image Processing & NURBS Generation






Multi-scale Analysis




$$\mathbf{\varepsilon} = \mathbf{\varepsilon}_h + \mathbf{\varepsilon}_v \quad \mathbf{\varepsilon}_v(y) = \mathbf{\varphi}(y)\mathbf{\varepsilon}_h$$



Recover Process of the Multi-scale Analysis


N-Wheel

$$\mathbf{\varepsilon} = (\mathbf{I} + \mathbf{\varphi})\mathbf{\varepsilon}_h \qquad \mathbf{\sigma} = \mathbf{D}^{\varepsilon}\mathbf{\varepsilon}$$



Topology Optimization





Award Winning Technology: Function-Oriented Material Design (FOMD)

FOMD focuses on optimizing material distribution to align with the structural functions of a (vehicle) system, ensuring lightweight design and high performance.

Key Steps:

- Define Structural Functions: Clearly identify the functional roles of a structural element within the (air vehicle) system.
- 2. Quantify Objectives and Constraints: Translate these functions into measurable objectives and constraints for the optimization process.
- 3. Optimize Material Distribution: Utilize topology optimization and related techniques to achieve the most efficient design, balancing lightweight construction and superior performance.

ASME INTERNATIONAL

The American Society of Mechanical Engineers

Founded 1880

DESIGN ENGINEERING DIVISION VEHICLE DESIGN COMMITTEE

AWARDS THE
BEST PAPER AWARD
TO

Zheng-Dong Ma Hui Wang Nopboru Kikuchi Christophe Pierre Basavaraju Raju

IN TESTIMONY OF THE HIGH REGARD OF YOUR ASSOCIATES
AND THE DEEP APPRECIATION OF THE SOCIETY
FOR YOUR VALUED SERVICES IN ADVANCING
THE ENGINEERING PROFESSION FOR THE PAPER
"Function-Oriented Material Design for Next-Generation

Ground Vehicles"

at the
2003 ASME International Mechanical Engineering Congress
and Exposition






November 17, 2003


Imbedded Slicer for 3D Printing






Optimal 3D-Printing Pass Generation





Multi-scale 3D-Printing Infill Analyses






n-Wheel and Vehicle Integration (Next Step)




Developed at The University of Michigan



The simulation platform also provides new and advanced component design capabilities.


Using distributed simulation functionality, the simulation platform can quickly model vehicle behavior, which is key for modular vehicle design



Cloud-Based Distributed Simulation




Developed at The University of Michigan



Proposed Distributed Manufacturing



- Industrial IoT hardware and communication channels are now advanced enough to enable fast, real-time big data processing and interactive networks, supporting distributed manufacturing powered by digital twin technologies.
- Looking ahead, the integration of enhanced 5G technology and the continued evolution of industrial IoT hardware will make digital twins ubiquitous across industries.







PART-IV

Digital n-Wheel

Definition of the Digital Twin for the n-Wheel



- Self-Contained Digital Model: A complete virtual representation of the n-Wheel, encompassing all substructure modules and their physical characteristics.
- Precise Physical Correlation: Accurately mirrors the geometry, dimensions, and subsystems of the corresponding physical unit.
- Integrated Performance Data: Includes all critical physical properties for assessing performance, durability, and cost of the unit and its components.
- Manufacturing and Process Intelligence: Provides detailed information on manufacturing, assembly, and related processes.
- Real-Time Modularity: Easily decomposable and reassemblable within the virtual space for instantaneous analysis, evaluation, and optimization of the entire unit and its subsystems.
- **Immersive Virtual Interaction:** Offers a realistic user experience through VR technologies, enabling visual, auditory, and tactile interactions in simulated environments like proving grounds.
- Comprehensive Virtual Testing: Facilitates robust testing and simulations across various virtual testing platforms.
- Full Lifecycle Simulation: Supports end-to-end simulation of the unit's lifecycle, from development to decommissioning.


Objective of the Digital n-Wheel



- Efficient and fast design of various products.
- Easy to use, simple to understand, usable by ordinary people.
- Graphical input, parametric, modular.
- CAD-CAE integrated simulation, design, and optimization.
- Aesthetic design.
- Output optimized 3D CAD models directly.
- Direct connection to CNC machining and 3D printing.
- Achieve optimized design, lightweight and low cost.
- Achieve personalized products and customer customization.
- Realize forward design!


Layout of the Digital n-Wheel





Parameterization of the Digital n-Wheel






7) Redesign ID

Graphic User Interface of the Digital n-Wheel


N-Wheel





Parametrized, IGA-based, CAD-CAE-CAM integrated, with optimization techniques!

Digital n-Wheel Processes










1) Parameter Identification

2) Topology Optimization

3) Full n-Wheel Modeling






| Cyrs | Schooler | Cyrs | Cyr


5) Nonlinear Analysis


6) 3D-Printing Slicing

Modeling Options of the Digital n-Wheel












1) Cell

2) Panel

3) metaTire







4) Rim

5) Topology Optimizer

6) Full n-Wheel Design

 Cell
 Panel
 meta-Tire
 Rim
 n-Wheel
 Optimizer
 3D Slicer

Parameter Identification of the Tread







Photo any existing tread and generate 3D NURBS model automatically for IGA.

Topology Design of the metaTire






Varied number of layers with varied number of cells in the layer

Topology Optimization of the Rim






From a blank sheet to optimal layout to 3D NURBS model!

Rim-Integrated n-Wheel Design






Varied rim types of the n-Wheel design


Example Auto-generated Tread Designs





Example Modal Analysis





Graphic User Interface of the digital n-Wheel for modal analysis

Comparison of metaTire[™] and Rubber Tire



> First 9 modes of metaTire



1) 75.9 Hz



2) 76.7 Hz



3) 76.8 Hz

First 9 modes of rubber tire (Air Pressure at36 psi)



1) 15.7 Hz



2) 46.0 Hz



3) 46.8 Hz



4) 76.8 Hz



5) 79.5 Hz



6) 88.3 Hz



4) 84.6 Hz



5) 87.2 Hz



6) 87.3 Hz



7) 88.3 Hz



8) 88.4 Hz



9) 100.0 Hz



7) 90.0 Hz



8) 97.3 Hz




9) 101.4 Hz

Lower eigenfrequencies of the metaTire are significantly higher than rubber tire


1st-3rd Modes of a NPR Runflat




➤ 2nd Order Model




Modal Stresses:





1) 78 Hz





2) 79 Hz






3) 79 Hz

Example Nonlinear Analysis






Parametrized, IGA-based, CAD-CAE-CAM integrated!


Stiffening Effect of the metaTireTM







Optimal Designs for Rim Configurations












1) Design A

2) Design B

3) Design C







4) Design D


5) Design E

6) Design F

For different loading conditions and weight constraints

Size Optimization of the n-Wheel






All critical design variables are fully optimizable!


Infill Material Optimization for 3D Printing






Capable for Designing Pneumatic Tires







1) Modal analysis of pneumatic tire (36 psi)



2) Modal analysis of pneumatic tire with rim



3) nonlinear analysis of pneumatic tire with rim



- Tire air pressure = 36 psi
- 4) CAD model of the deformed pneumatic tire

Next Version n-Wheel



Sensors and adaptive control ensure optimal performance in all climates and terrains.

> Features:


- Variable tread for speed and surface adaptability.
- Reduced rolling resistance for better fuel efficiency.
- Variable stiffness for comfort and noise reduction.


> Benefits:


- Simplifies design, lowers costs, and supports green production.
- Powers autonomous driving with intelligent tracking.

Potential Manufacturing Processes











(a) Parts Assembling

b) Injection Molding

c) Future 3D-Printing




PART - V


Technology Validation

Comparison with Testing Results











Comparison of Simulation and Testing Results



Polymaker PolyMide CoPA






- Material: Polymaker PolyMide CoPA (Nylon)
- 3D Printing method: FDM
- TYPE I specimen weight: 8 g
- TYPE V specimen weight: 1.5 g
- Calculated material density: 1.0 g/cc
- Maximum force for TYPE-I: 250.3 Kg
- Maximum force for TYPE–V: 64 Kg



- Measured material tensile strength: 60 MPa.
- Sample scale: 0.316
- Measured sample weighs: 227 g (convert to the full runflat weight: 47.5 lbs.)
- Measured force: 801 Kg (no damage) (convert to full runflat load: 17,647 lbs., exceed the required maximum load by 53%)

Comparison of N-wheel with Punctured Solid Tire





1, Pneumatic tire (45PSI)

2, N-Wheel

3, Solid tire with holes

The vertical axis is the applied force (up to 100 kg) and the horizontal axis is the amount of deformation of the tire (a large amount of deformation indicates a good degree of comfort). The results of this test show that our tires can be more comfortable than the solid tire with holes. The results also show that our tires have a better bearing capacity than conventional inflatable tires because they can harden when the load is heavy. Our tires also have the advantage of lighter weight and cheaper prices than the solid tires.


Future of the n-Wheel



- A High-performance tire-wheel integrated unit for advanced mobility.
- Innovative designs beyond imagination of traditional rubber tires.
- > Never runflat, puncture-free, and maintenance-free.
- Improved vehicle performance in multidisciplinary areas.
- Reduced wheel weight and achieving better vehicle mileage.
- Function-oriented design for traction, mobility and drivability
- Sensor-embedded smart tires for autonomic drives and next generation mobilities.


Potential i-Wheel Applications





Intelligent n-Wheels (i-Wheels) Concept










Application for Terrain Identification

n-Wheel with Adaptive Smart Tread


Internal Structure of the n-Wheel Variable Tread System Concept





Fully Automated Assembly Line Concept for n-Wheels





Inventor Dr. Z.D. Ma



Education:

Ph.D. in Mechanical Engineering, Kyoto University, Japan, 1989

- Professional Positions:
- Research Scientist Emeritus, University of Michigan
- Fellow, American Society of Mechanical Engineers (ASME)
- Owner, N-Wheel Technologies, Inc. (since 2001)
- Publications & Innovations:
- Published over 180 high-quality technical articles
- Reached 4,500 citations
- Awarded 12 patents
- > Awards & Honors:
- Recipient of several prestigious international awards
- Outstanding Research Scientist Award, University of Michigan, College of Engineering (2004-2005)
- > Research Leadership:
- Secured and managed research projects totaling over \$8 million across various disciplines



Get Ready ...





➢ Get ready for the nextgeneration N-Wheel, engineered for passenger cars and poised to outperform Michelin's Uptis!







